



product details

64638 HLX 100W 24V G6,35 FS1



Product description: 64638 HLX 100W 24V G6,35 FS1
Product code: 4050300283050
Quantity: Folding carton box (FS) contains 1 Piece (PCE)

You can find this product in the eCatalog:

http://catalog.myosram.com?~language=EN&~country=COM&it_p=4050300283050

Applications	
Burning position	any

Categorizations	
NAED	53998

General Description	
Base (standard designation)	G6.35

Logistical Data	
Product weight	3.100 g

Technical - Electrical Data	
Construction wattage	100 W
Construction voltage	24 V
Lamp wattage	100 W
Lamp voltage	24 V
Nominal wattage	100 W
Nominal voltage	24 V

Technical - Geometries	
Diameter	13unece.unit.MMT
Filament length	5.30 mm
Light centre length (LCL)	30 mm
Illuminated field	5.3*2.6 mm²
Length	50.00 mm
Filament diameter	2.6 mm

Technical - Lifespan	
Lifespan	300 h

Technical - Light Technical Data	
Luminous flux	2900 lm
Color temperature	3350 K

Packaging units				
Product code	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume
4050300283050	Folding carton box contains 1 Piece	25,000 mm x 23,000 mm x 70,000 mm	6,333 g (0,000 g)	0,040 Cubic dec.
4050300890739	Shipping carton box contains 40 Piece	121,000 mm x 107,000 mm x 144,000 mm	245,000 g (0,000 g)	1,864 Cubic dec.

Some lamp models are available as XENOPHOT versions (type HLX).

With xenon instead of krypton as the filler gas, a luminous flux up to 10 % higher is achieved with the same electrical lamp data.



27.06.2011

Subject to change without notice. Errors and omission excepted.

© 2011 OSRAM GmbH

Page 1 of 1