



product details

64655 HLX 250W 24V G6,35 FS1



Product description: 64655 HLX 250W 24V G6,35 FS1
Product code: 4050300006734
Quantity: Folding carton box (FS) contains 1 Piece (PCE)

You can find this product in the eCatalog:

http://catalog.myosram.com?~language=EN&~country=COM&it_p=4050300006734

Applications	
Burning position	s90

Categorizations	
ANSI code	EHJ
LIF	A1/223
NAED	54254

General Description	
Base (standard designation)	G6.35

Logistical Data	
Product weight	4.070 g

Technical - Electrical Data	
Construction wattage	250 W
Construction voltage	24 V
Lamp wattage	250 W
Lamp voltage	24 V
Nominal wattage	250 W
Nominal voltage	24 V

Technical - Geometries	
Diameter	12.5unece.unit.MMT
Filament length	7.00 mm
Light centre length (LCL)	33 mm
Illuminated field	7.0*3.5 mm²
Length	55.00 mm
Filament diameter	3.5 mm

Technical - Lifespan	
Lifespan	50 h

Technical - Light Technical Data	
Luminous flux	10000 lm
Color temperature	3550 K

Packaging units				
Product code	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume
4050300006734	Folding carton box contains 1 Piece	25,000 mm x 23,000 mm x 70,000 mm	13,455 g (0,000 g)	0,040 Cubic dec.
4050300890807	Shipping carton box contains 40 Piece	121,000 mm x 107,000 mm x 144,000 mm	283,800 g (0,000 g)	1,864 Cubic dec.





product details

64655 HLX 250W 24V G6,35 FS1

Some lamp models are available as XENOPHOT versions (type HLX).
With xenon instead of krypton as the filler gas, a luminous flux up to 10 % higher is achieved with the same electrical lamp data.